



BELCO CABLE SERIES

CJTT50 - 5T ATM Dual Drum Tag Trailer

Description

The Belco CJTT50 is a purpose-built 5T ATM dual drum tag trailer designed for the simultaneous transport and over-the-back deployment of two cable drums. Built to AS3990 and AS1554 Part 1 Grade SP, it features a heavy-duty fixed-axle chassis with manual spindle loading and zinc plated locking and centring collars. Suited to operations where a reliable, no-frills cable transport solution is required.

Key Features

- Carries two cable drums simultaneously — up to 2.2m diameter x 1.3m wide each
- ~3T payload capacity across both drums
- Manual loading via 2x spindles with zinc plated locking and centring collars
- Over-the-back cable deployment
- Fixed axles, 3T rated each — 150 x 150 x 5mm RHS chassis
- Class 2.5 sandblast prep, epoxy zinc primer, Weathermax HBR acrylic polyurethane finish
- 6-year warranty on drawbar and chassis
- Built to AS3990 & AS1554 Part 1 Grade SP



Specifications - 5T ATM Dual Drum Tag Trailer

DIMENSIONS

Design Standard	AS3990
Weld Standard	AS1554-Part 1 (SP)
Overall Length	~2,300 MM
Overall Width	~3,900 MM
Weight (Tare)	~1,850 KG

CAPACITY

Maximum Cable Drum Weight	*3,000KG
ATM	5,000 KG
Drum Diameter Capacity	2,200 MM
Drum Width Capacity	1,300 MM
Spindle	(D) 75MM (can modify)

*across both drums

Brakes	12" Dexter Electric
Tyre Size	Brakes235/85/R15

CONSTRUCTION

Chassis	150 x 150 x 5 RHS
Drawbar	Hinging 89 x 89 x 5 SHS
Centring Collars	Zinc Plated
Locking Collars	Zinc Plated Bolt Up
Jockey Wheel	1 x Sidewind Jackleg

RUNNING GEAR

Suspension	None (Fixed Axles to Chassis)
Axles	3T Each
Rims	6 Stud, White Steel
Tyres	235/85/R15

OPERATING

Loading	Manual (2 x Spindles)
Cable Deployment	Over the back
Drum Drive	None

GENERAL

Lighting	None
Coupling	40mm Ring Feeder
Safety Chains	None
Trailer Plug	None
Spare Wheel	None
Mudguards	2.1mm Checkerplate
Handbrake	None

Warranty

Drawbar and Chassis	6 Years
---------------------	---------

